



## Product Specification Sheet

EL-GPP / EB-GPP

# LABEL-HOUSE

**Permanent, coated high gloss white paper labels  
on sheet for inkjet, thermal transfer, full-color copying machines and laser  
printers**

### Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	102 (+/- 6)	micron	ISO 534
Adhesive	18	micron	
Liner	91	micron	

### Adhesive (acrylic):

		Value	Unit	Test Method
Shear Strength		*		
Initial Tack		*		
Peel Resistance	Stainless Steel	*		
	Glass	*		
	Polypropylene	*		
	Paint (automotive)	*		
	PBT	*		
Application Temperature		min. +5	°C	
Temperature Range (Adhesive)		-40 to 80	°C	

\*no information provided by the manufacturer

**Certifications:** Material meets REACH and RoHS requirements (2011/65/EU). Adhesive is approved by ISEGA (Direct contact dry & moist, non fatty foodstuffs) according to the German Recommendations XIV.IMDS data available.

**Printability:** Suited for full-color copying machines, inkjet and laser printers. Print methods tested: water based inkjet and pigmented inks. Each application should be tested and tuned individually.

**Storage:** Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

**Further Information:** n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: March 2017.