



Product Specification Sheet

EBL_._SR / EL-SR / EB-SR / EBL-SR_._-500

LABEL-HOUSE

**Permanent, glossy silver polyester labels
on sheet for monochrome copying machines and laser printers**

Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	58	micron	DIN 53370
Adhesive	20	micron	
Liner (kraft paper)	97	micron	ISO 534

Adhesive (acrylic):

		Value	Unit	Test Method
Shear Strength		10	hours	FTM 8
Initial Tack		9,0	N/25 mm	FTM 9
Peel Resistance	Stainless Steel	*		
	Glass	*		
	Polypropylene	*		
	Paint (automotive)	*		
	PBT	*		
Application Temperature		min. +5	°C	
Temperature Range (Adhesive)		-20 to +100	°C	

*no information provided by the manufacturer

Certifications: Material meets REACH and RoHS requirements (2011/65/EU).

Printability: Specially designed laser printable material for product, logistics and industrial variable information applications. It can be also used in address labelling or other information labelling with difficult environmental conditions in SOHO end-uses for demanding substrates needing high adhesion properties. Due to the pre-treatment, the film is printable by common label printing methods. Special inks should be used. Suited for monochrome laser and thermal transfer.

Storage: Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

Further Information: n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: October 2016.