



Product Specification Sheet

EL_._PPOP / EB_._PPOP / EB_._PPOP500

LABEL-HOUSE

**Permanent, matte white opaque writing paper (satined) labels
on sheet for full-color copying machines and laser printers**

Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	71 (+/- 3)	micron	DIN EN 20534
Adhesive	18	micron	
Liner (glassine)	55	micron	

Adhesive (acrylic):

	Value	Unit	Test Method
Shear Strength	*		
Initial Tack	*		
Peel Resistance	Stainless Steel	*	
	Glass	*	
	Polypropylene	*	
	Paint (automotive)	*	
	PBT	*	
Application Temperature	min. +5	°C	
Temperature Range (Adhesive)	-20 to +80	°C	

*no information provided by the manufacturer

Certifications: Material meets REACH and RoHS requirements (2011/65/EU). IMDS Data available.

Printability: Suited for full-color copying machines and laser printers.

Storage: Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

Further Information: n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: March 2016.