

## Product Specification Sheet

ERJ-PP / EFJ-PP

# LABEL-HOUSE

**Permanent, coated matte white paper labels  
on roll for inkjet, thermal transfer, full-color copying machines and laser  
printers**

### Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	83 (+/- 4)	micron	ISO 534
Adhesive	18	micron	
Liner (glassine)	55	micron	

### Adhesive (acrylic):

		Value	Unit	Test Method
Shear Strength		*		
Initial Tack		*		
Peel Resistance	Stainless Steel	*		
	Glass	*		
	Polypropylene	*		
	Paint (automotive)	*		
	PBT	*		
Application Temperature		min. +5	°C	
Temperature Range (Adhesive)		-20 to +80	°C	

\*no information provided by the manufacturer

**Certifications:** Material meets REACH and RoHS requirements (2011/65/EU) and is approved for direct and indirect contact with dry and moist, non-greasy foodstuffs (ISEGA).EN 71/3 toy-security norm.

**Printability:** The paper is printable with common dye and pigmented inks as well as latex inks. Suited for thermal transfer printing with wax ribbons (i.e. Armor AWR®8, AWR®470, AWP®FH; Kurz K100N; Zebra 2100, 2300) or combination ribbons (i.e. Armor APR®6, APX®FH; Kurz K200, K305; Zebra 3200, 3400).

**Storage:** Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

**Further Information:** n/a

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: April 2016.