



## Product Specification Sheet

### ERT-MP / EF-MP

Printable with wax/resin ribbon (FTA-LM...x...) for coated paper labels

# LABEL-HOUSE

**Permanent, coated matte white paper labels  
on roll for thermal transfer printers**

#### Material Thickness:

	Value (Tolerance)	Unit	Test Method
Facestock	65	micron	
Adhesive	15	micron	
Liner (glassine)	54	micron	

#### Adhesive (acrylic):

		Value	Unit	Test Method
Shear Strength		120	min	
Initial Tack		1600,0	g/25 mm	
Peel Resistance	Stainless Steel	*		
	Glass	*		
	Polypropylene	*		
	Paint (automotive)	*		
	PBT	*		
Application Temperature		min. +5	°C	
Temperature Range (Adhesive)		-20 to +80	°C	

\*no information provided by the manufacturer

**Certifications:** The material is REACH and RoHS Compliant; Adhesive approved for indirect food contacts and corresponding to UNI -EN 71/3 toy safety regulations. Paper from sustainable forestry (FSC certified).

**Printability:** Suited for thermal transfer printing with wax ribbons (i.e. Armor AWR®8, AWR®470, AWX®FH; Labelident Eco wax; Zebra 2100, 2300) or combination ribbons (i.e. Armor APR®6, APX®FH; Kurz K200, K305; Zebra 3200, 3400).

**Storage:** Material is stable for two years stored at max. 21°C and 50% rel. humidity. Damp conditions, excessive heat and/or cold conditions should be avoided.

**Further Information:** Ideal for multicolor prints requiring exceptional contrast and great detail. Liner designed for automatic label generation. Ideal for photocells dispensing system.

Note: All values are guidelines and not intended for use in setting specifications. The information provided does not constitute any warranty, express or implied, and is intended solely for the recipient and shall not be forwarded to any third party. The buyer of our products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. Samples of our materials can be provided upon request. Information is subject to change without prior notification. Last Updated: January 2019.